

# BYTEM-103-PC

Panel PC - 10.4" - Processeur Intel® Atom™ E3845 - Certifié EN50155 - Dalle tactile PCAP



10"



## Points forts

- Certification EN50155
- Face avant IP65 & Châssis IP54
- Design True-Flat
- 1 x M12 LAN port
- Entrée 24VDC - Connecteur M12
- Options : 48VDC/72VDC/110VDC
- Clavier membrane programmable
- Kit rackable



## Spécifications

Panel Type	10.4" TFT-LCD
Résolution	1024 x 768
Contrast Ratio	1000:1
Angles de vues	176/176
Backlight	50000(H)
Luminosité	500 cd/m <sup>2</sup>
Dalle tactile	Projected capacitive, 2x points
CPU Type	Intel® Atom™ Processor E3845 (Quad-Core @ 1.91GHz)
Memory	2x DDR3L SO-DIMM, up to 8GB, default DDR3L 4GB (4GBx1)
LAN	1x 10/100 LAN with M12 connector
Expansion Slots	1x mPCI-E(x1) w/ USB signal [half-size] 1x mSATA/mPCI-E(x1) w/ USB signal and mSATA supports [full-size]
I/O Interface	1x USB 3.0 2x USB 2.0 (Type-A + M12) 1x RS232/422/485
Power Requirement	4-pin M12 connector 24V DC (default) power input, Optional 48V DC 72V DC & 110V DC
Construction	Aluminum front bezel and back cover IP65 front bezel/ Others IP40 not including I/O cover/ IP54 for all with I/O cover
Weight	4.3 kgs
Chassis	Silver/Silver
Storage	1x 2.5" SATA
Mounting	Wall mount and VESA 75x75, 100x100 mm
Dimensions	275mm(W) x 238.5mm(D) x 78.5mm(H) 10.82"(W) x 9.38"(D) x 3.09"(H)
Operating Temperature	-40°C~70°C (EN50155-TX)
Storage Temperature	-40°C~70°C
Relative Humidity	10%~90% (non-condensing)
Vibration	IEC61373
Certification	CE/FCC Class B EN50155-TX
Operating System	Windows 8 32/64 bit, Windows 7 Pro for Embedded 64 bit, WES7 64 bit

## Référence de Commande

BYTEM-103-PC	10.4" (1024 x 768) Flat Panel Design Panel PC with I8897, Intel® Atom™ Processor E3845 1.91GHz, 4GB DDR3L SO-DIMM, 64G SSD, projected capacitive touch, w/o power adaptor
Adaptateur Alim.	Adaptateur AC Entrée 100V~240V - 24VDC sortie 90W - A005PS090W0100600P

## Dimensions

