
PAC-1700G 7-slot Full-size Compact Chassis



CD-ROM and HDD are not included in package.

Features

- RoHS compliant design
- One 5.25" and one 3.5" drive bay
- Two 3.5" internal HDD bays
- Seven expansion slots, compatible with full-size SBC
- 7 expansion slots, compatible with full-size SBC

Specifications


◆ Construction	Metal with plastic front panel			
♦ SBC Form Factor	Full-size, slot CPU card			
♦ Drive Bays	1 x front-accessible 3.5"			
	1 x 5.25"			
	2 x 3.5" HDD			
♦ Cooling Fans	1 x 8 cm			
♦ I/O Openings	1 x LPT, 2 x COM			
♦ Expansion Slots	7 slots			
♦ Indicators	Power, HDD			
♦ Button	Power switch, reset			
♦ Operating Temperature	0°C ~ 50°C			
♦ Operating Humidity	10% ~ 90%			
♦ Color	B: Black			
♦ Weight (Net/Gross)	6 kg/8.4 kg			
♦ Dimensions (DxWxH)	433 mm x 233 mm x 253.7 mm			

Ordering Information

Part No.	Description
PAC-1700GB-R20/A130C	7-slot full-size compact chassis, black, 1 x 8 cm fan, with ACE-A130C-R10 (300W ATX model), RoHS



Dimensions (Unit: mm)



Backplane Options

Model No.	SBC Tuno	PCI IS	ICA	PCle				PSU Connector
Model No.	SBC Type		ISA	x1	х4	x8	x16	F30 Connector
PCI-7S-RS	PICMG 1.0	4	3	0	0	0	0	AT/ATX
PE-7S*	PICMG 1.3	3	0	2	0	0	1	ATX
PE-7S2*	PICMG 1.3	1	0	4	0	0	1	ATX
HPXE2-7S1	HPCIE	3	0	0	0	2	0	ATX

^{*}Only R20 or later versions support PICMG 1.3 backplane

Power Supply Options

Туре	Model No.	Watt
ATX	ACE-A130C-R10	300W
	ACE-A140A-S-R11	400W

PAC-1700G supports single PS/2 PSU. For more IEI PSU models, please refer to section 5 or visit www.ieiworld.com.